



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx EESF 20.0018X	Page 1 of 4	<u>Certificate history:</u>
Status:	Current	Issue No: 2	Issue 1 (2021-12-09) Issue 0 (2020-08-28)
Date of Issue:	2023-02-02		
Applicant:	Valmet Flow Control Oy Vanha Porvoontie 229 Vantaa FI-01380 Finland		
Equipment:	VG9000F ("ValvGuard") series safety valve controllers. VG9200F series, types VG92..FX.. and VG9300F series, types VG93..FX..		
Optional accessory:	See Annex		
Type of Protection:	Intrinsically safe		
Marking:	Ex ia IIC T6...T4 Ga Ex ia IIIC T95 °C...T125 °C Da Ex ib IIC T6...T4 Gb Ex ib IIIC T95 °C...T125 °C Db		

Approved for issue on behalf of the IECEx
Certification Body:

Jenni Hirvelä

Position:

Senior Expert

Signature:
(for printed version)

Date:
(for printed version)

2023-02-02

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

Eurofins Electric & Electronics Finland Oy
Kivimiehentie 4
Espoo FI-02150
Finland





IECEx Certificate of Conformity

Certificate No.: **IECEx EESF 20.0018X**

Page 2 of 4

Date of issue: 2023-02-02

Issue No: 2

Manufacturer: **Valmet Flow Control Oy**
Vanha Porvoontie 229
Vantaa FI-01380
Finland

Manufacturing
locations: **Valmet Flow Control Oy**
Vanha Porvoontie 229
Vantaa FI-01380
Finland

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

[IEC 60079-11:2011](#) Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[FI/EESF/ExTR20.0019/01](#)

Quality Assessment Report:

[NO/DNV/QAR09.0008/13](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx EESF 20.0018X**

Page 3 of 4

Date of issue: 2023-02-02

Issue No: 2

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

VG9000F ("ValvGuard") series safety valve controllers are intended to control on/off valves in hazardous industrial areas. FISCO compliant Fieldbus protocol has been utilized in the controllers. In addition with distributed control system (DCS), the Fieldbus is used for supplying power to assigned functions of the equipment, e.g. for diagnostics and valve control. Separate intrinsically safe 24V Safety Control input is used in case of emergency situation for overriding all other tasks. The equipment accommodates three component boards (FBI, SVC and SA 4W), LUI (Local User Interface) module, prestage unit and limit switches (option).

The maximum input values of Fieldbus interface:

$U_i \leq 24 \text{ V}$ $I_i \leq 380 \text{ mA}$ $P_i \leq 5.32 \text{ W}$ $C_i < 5 \text{ nF}$ $L_i < 10 \text{ }\mu\text{H}$

(The values comply with the requirements for FISCO Field devices in IEC 60079-11)

The maximum input values of 24 V Safety Control input:

$U_i \leq 28 \text{ V}$ $I_i \leq 150 \text{ mA}$ $P_i \leq 1 \text{ W}$ $C_i < 15 \text{ nF}$ $L_i < 175 \text{ }\mu\text{H}$

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. The maximum allowed ambient temperature ranges according to applied T-classes are:
 - $T_{amb} -40 \text{ }^\circ\text{C} \dots +50 \text{ }^\circ\text{C}$ for T6 or T95 $^\circ\text{C}$
 - $T_{amb} -40 \text{ }^\circ\text{C} \dots +65 \text{ }^\circ\text{C}$ for T5 or T110 $^\circ\text{C}$
 - $T_{amb} -40 \text{ }^\circ\text{C} \dots +80 \text{ }^\circ\text{C}$ for T4 or T125 $^\circ\text{C}$
2. The permissible ambient temperature range depends on the used configuration. The ambient temperature range is marked on the identification plate.
3. At an ambient temperature $\geq +70 \text{ }^\circ\text{C}$, the temperature rating of the connection cable shall be in accordance with maximum ambient temperature range.
4. For Equipment protection level EPL Ga, the enclosure parts or enclosures made of aluminium alloy shall not be subjected to friction or impacts due to spark ignition hazard.
5. The safety valve controller shall be connected according to manufacturer's instructions.
6. The safety valve controller shall not be subject to prolific charge generating mechanism by dust.



IECEx Certificate of Conformity

Certificate No.: **IECEx EESF 20.0018X**

Page 4 of 4

Date of issue: 2023-02-02

Issue No: 2

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Documentation updated, company name changed to Valmet Flow Control Oy and editorial corrections.

Annex:

[ANNEX TO IECEx EESF 20.0018X and IECEx EESF 20.0019X_1.pdf](#)

ANNEX TO IECEX EESF 20.0018X and IECEX EESF 20.0019X

**VG9200F series, types VG92..FX.. and
VG9300F series, types VG93..FX..**

Product type marking nomenclature:

Brands 1	Diagnostic variants: 2	Enclosures: 3	Spool valve sizes: 4	Communication: 5	Approval 6	Options: 7	Limit switch type: 8
VG -> ValvGuard	9 -> Intelligent Valve controller	2 -> Die cast aluminum. alloy 3 -> Stainless steel	12 -> Restricted capacity 15-> Standard capacity. 35 ->High capacity. 37 -> Extended capacity.	F -> Foundation Fieldbus H1	X -> IECEX / ATEX certified product	J -> External Junction box (Table 1.)	Ref. Table 2.

Table 1. Option J Junction Box types by International Metal Engineering Pte

IME 7080AM-03-22 or IME 7080TM-03-22 (IECEX SIR 07.0111U Issue 3.)
Ex d IIC Gb / Ex tb IIIC Db IP68; Ta = -40°C to +85°

Table 2. Optional Inductive Limit Switch types for the certified types:

Note! Limit switch's temperature range and electrical data must be verified from its certificate

Neles type code	Manufacturer of switch	Type of switch	ATEX and IECEX certifications of switch		Classification	Electrical data					T _{amb}			
						Ui (V)	Ii (mA)	Pi (mW)	Li (μH)	Ci (nF)	T _{min} (C)	T6 (C)	T5 (C)	T4 (C)
I02	Pepperl+Fuchs	NJ2-12GK-SN (2 pcs)	PTB 00 ATEX 2049X	IECEX PTB 11.0092X	II 1 G Ex ia IIC T6...T1 Ga	16	25	64	150	50	-40	50	64	80
					II 2 G Ex ia IIC T6...T1 Gb	16	52	169	150	50	-40	50	65	80
I09	Pepperl+Fuchs	NCB2-12GM35-N0 (2 pcs)	PTB 00 ATEX 2048X	IECEX PTB 11.0037X	II 1 G Ex ia IIC T6...T1 Ga	16	25	64	100	90	-25	50	65	80
					II 2 G Ex ia IIC T6...T1 Gb	16	52	169	100	90	-25	50	65	80
					II 2 G Ex ia IIC T6...T1 Gb	16	52	169	150	70	-50/-40 ⁽²⁾	50	65	80
					II 1 G Ex ia IIC T6...T1 Ga	16	25	64	200	70	-25	50	64	80
I45	Pepperl+Fuchs	NJ3-18GK-S1N (2 pcs)	PTB 00 ATEX 2049X	IECEX PTB 11.0092X	II 2 G Ex ia IIC T6...T1 Gb	16	52	169	200	70	-25	50	65	80
I57	Pepperl+Fuchs	NJ2-V3-N (2 pcs)	PTB 00 ATEX 2032X	IECEX PTB 11.0021X	II 1 G Ex ia IIC T6...T1 Ga	16	25	64	50	40	-25	49	61	80
					II 2 G Ex ia IIC T6...T1 Gb	16	52	169	50	40	-25	45	60	80
I58	Pepperl+Fuchs	NJ2-V3-N (4 pcs)	PTB 00 ATEX 2032X	IECEX PTB 11.0021X	II 1 G Ex ia IIC T6...T1 Ga	16	25	64	50	40	-25	49	61	80
					II 2 G Ex ia IIC T6...T1 Gb	16	52	169	50	40	-25	45	60	80
R02 ¹⁾	StoneL	Maxx-Guard M, SPDT (2 pcs)	n/a	n/a	n/a	30	100	2000	800	66	-40	50	65	80
T01 ¹⁾	Neles	Position transmitter	n/a	n/a	n/a	30	120	1000	100	66	-40	45	60	80

1) StoneL Maxx-Guard M reed switch proximity sensors (R02) and Neles Position transmitter (T01) have been assessed for the certified valve controller types in the related ExTR.