



Reg No: 1999/027771/07

(Pty) Ltd

7 Spanner Rd / PO Box 467
Olifantsfontein
1665

Tel: +27 (11) 316 4601

Fax: +27 (11) 316 5670

E-mail: admin-mgr@explolabs.co.za

GOVERNMENT APPROVED TEST LABORATORY

IN TERMS OF ARP 0108: "REGULATORY REQUIREMENTS FOR EXPLOSION PROTECTED APPARATUS"

IA CERTIFICATE

Date Issued: 01 Jan 2020

*Expiry date: 01 Jan 2023

Page 1 of 3

Issue: 1

Ex – Type Examination Certificate

Certificate Number: **S-XPL/19.0449 X**
Equipment: **Valve Position Sensor**
Model / Type: **Series HX**
Applicant: **Neles South Africa (Pty) Ltd**
PO Box 264114
Three Rivers
1935

Manufacturer: **StoneL**

Serial No: All serial numbers imported between issued- and expire date and all serial numbers covered by a valid report or acceptable product certification mark.

Supplied by
Neles South Africa (Pty) Ltd
Identified by Inspection Authority number
S-XPL/19.0449 X

And as described in the Explolabs file number **XPL/20424/19.0449** is hereby certified "Explosion Protected (Refer to clause 1, for Ex Rating)", having been examined and inspected in accordance with the relevant requirements of South African Standards.

SANS 60079-0: 2012 Ed 5

IEC 60079-0: 2011 Ed 6

Explosive atmospheres Part 0: Equipment — General requirements

SANS 60079-11: 2012 Ed 4

IEC 60079-11: 2011 Ed 6

Explosive atmospheres Part 11: Equipment protection by intrinsic safety "i"

Risk of ignition provided:

Protection afforded	Equipment Protection Level (EPL)	Performance of protection	Conditions of operation	T class or Max Surface Temp (°C)
	Group			
Very high	Ga Group II	Two independent means of protection or safe even when two faults occur independently of each other	Equipment remains functioning in zones 0, 1 and 2	T5 (100 °C) T6 (85 °C)
Very high	Da Group III		Equipment remains functioning in zones 20, 21 and 22	T100 °C

This certification indicates compliance with R10.1 of the Mines Health and Safety Act and/or EMR 9(2) of the Occupational Health and Safety Act, provided that the apparatus is used as relevant in accordance with:

- SANS 10086 and IEC/SANS 61241-14 requirements as applicable;
 - Any conditions mentioned in the above report;
 - Any relevant requirements and codes of practice enforced in terms of the Mine Health and Safety Act or Occupational Health and Safety Act; and
 - Any restrictions and conditions enforced by the Chief Inspector of Mines or the Principal Inspector or the Chief Inspector: Occupational Health and Safety.
- v) A revision certificate replaces all previous version of the certificate.
vi) * - Only covers equipment Imported between the "Issued" and "Expire" dates.
vii) If and when your QAN (Quality Assurance Notification) Certificate for your equipment manufacturer expires during the valid period of the IA Certification (issued for your equipment) and a new certificate is not submitted the existing IA Certification will then be cancelled. It is thus the client's responsibility to always submit the updated and valid QAN certificate(s) to Explolabs (Pty) Ltd

DOCUMENT No: XPL0213 | RELEASE DATE: 29/05/2018 | REV : 7

This report supersedes all previous documents bearing the reference no XPL/20424/19.0449.

1. GENERAL

The marking of the Valve Position Sensor shall include the following:

Ex ia IIC T5 Ta=-40°C to +80°C Ga

Ex ia IIC T6 Ta=-40°C to +65°C Ga

Ex ia IIIC T100 °C Ta=-40°C to +80°C Da

IP66 / IP68

See Section 1 for specific applicability

See also FM15ATEX0038X for Series HX with Types of Protection “d” and “t”.

Description of Equipment or Protective System:

General - The Hawkeye Series HX Magnetic Proximity Sensor is intended for point sensing in an explosive atmosphere. The sensing head triggers on a magnetic target at distances up to 4-6 mm, depending on target material.

Construction - The sensor body is machined from 316 stainless steel.

Field Wiring – For the Level of Protection “ia” models, an integral cable is provided with or without a cable gland, Cooper Capri Type ADE1N0502SSS.

Gaskets and Seals – Silicone seals in the cable gland, rated -60°C to +140°C, are employed to provide IP66 / IP68 (3 m / 48 h) ingress protection.

The specific models described by this Certificate are as follows:

HXaTcSe-xxx. Valve Position Sensor.

a = Function 45.

c = Junction 01, 02, or 03.

e = Branding A or M.

xxx = Options “Special Unit Digits”

Note: ‘Special Unit Digits’ do not affect the integrity of the housing, the electrical safety, or the title plate.

Based on the following documentation: FM 15 ATEX 0045X up to Supplement 1

2. INSTALLATION INSTRUCTIONS

It is the manufacturer’s responsibility to supply installation instructions with each unit offered for sale as required by IEC/SANS 60079-0 Clause 30.

3. SPECIAL CONDITIONS FOR SAFE USE *(denoted by “X” after certificate number)*

- The integral supply cable shall be mechanically protected and terminated in a suitable terminal or junction facility.
- Using the box provided on the HX45T03 nameplate, the user shall permanently mark the Type of Protection chosen for the specific installation. Once the Type of Protection has been marked it shall not be changed.
- The earth bonding connection shall be maintained by either the external mounting thread and/or the earthing wire of the integral cable.

4. SCHEDULE OF LIMITATIONS *(denoted by “U” after certificate number)*

None.

5. CONDITIONS OF CERTIFICATION

All production units must be covered by a QAN (Quality Assurance Notification), Product Mark Scheme or batch evaluation.

6.

MARKING

The following (or similar) information have to be clearly and permanently marked on all units:

Supplier : Neles South Africa (Pty) Ltd
Manufacturer : StoneL
Equipment : Valve Position Sensor
Model/Type : Series HX
Serial No. : ---
Ex Rating : Ex ia IIC T5 Ta=-40°C to +80°C Ga
Ex ia IIC T6 Ta=-40°C to +65°C Ga
Ex ia IIIC T100 °C Ta=-40°C to +80°C Da
IP66 / IP68
See Section 1 for specific applicability
See also FM15ATEX0038X for Series HX with Types of Protection “d” and “t”.

IA Certificate No : S-XPL/19.0449 X

Responsible Testing Officer:**P van Staden****Technical Specialist****EXPLOLABS EXPLOSION PREVENTION SERVICES**

This report/certificate shall not be reproduced except in full without the written approval of the company Explolabs (Pty) Ltd shall not be liable for any losses or damages sustained on account of any failure or omission to properly perform our duties in terms of any contract undertaken by us. This disclaimer is immutable and automatically incorporated in any contract undertaken by us; notwithstanding anything to the contrary, save for the express written waiver of our managing director. By marking the equipment in accordance with the documentation/standard, the manufacturer attests on his own responsibility that the equipment has been constructed in accordance with the applicable requirements of the relevant standards and that the routine verifications and tests have been successfully completed and that the product complies with the documentation and standard(s). The contents of electronic reports/certificates cannot be guaranteed. Original certification documents will be kept on file at Explolabs (Pty) Ltd