


The industry bench- mark for pumping

Flowrox™ pump solutions







We exist to make your life easier


Flowrox pumps serve a wide range of process industries. Hose pumps and progressive cavity pumps are specifically designed for demanding processes involving abrasive, corrosive, highly viscous or crystallizing media with high solids content. Our unique pump design saves energy and water increasing your process availability and reducing total cost of ownership.

- 1977** Pinch valves
- 2002** Peristaltic pumps
- 2008** Pump service, metering pumps
- 2011** Name changed from Larox Flowsys to Flowrox
- 2011** Progressive cavity pumps
- 2015** Pulsation dampeners
- 2017** Packaged pumping systems
- 2021** Flowrox brand acquired by Neles
- 2022** Valmet and Neles merged



We provide the optimal solution

Flowrox peristaltic pumps have the unique eccentric rolling hose compression. The rolling design extends the hose life time and simplifies maintenance.



Customer benefits

- Low total cost of ownership
- Low operating costs
- Improved process performance
- Long service intervals
- Minimized downtime
- Heavy duty design

Peristaltic pumps

Flowrox heavy duty hose pumps are designed for the toughest industrial applications. They are ideal for demanding processes involving abrasive, corrosive, viscous or crystallizing media with high solids content.

Advanced rolling design

The operating principle of the Flowrox hose pumps is based on the peristaltic effect. As the cylindrical rotor rotates along the hose, the process medium gets pushed forward through the hose. At the same time, the hose behind the compression point reverts to its original circular shape creating a suction effect at the pump inlet port. As a result, the hose bore is re-filled

with the medium. No backward flow or slip can occur as the hose is squeezed tight by the roller.

Due to their technical features, Flowrox hose pumps provide exact flow per revolution. They also incorporate an advanced rolling design, which eliminates friction, maximizes hose life and lowers energy consumption. Energy efficiency, long hose life and low

maintenance generates substantial savings during the life cycle of peristaltic pumps. Lifetime of Flowrox pumps' hoses is 3-5 times longer than conventional hose pumps.

Trailblazing pump technology

Flowrox LPP-T pumps are equipped with a patented hose flange and reliable in-line pipe connections, as well as a hose leak detection unit.

Flowrox heavy duty hose pumps from features to benefits

Rolling pump design



Save energy up to 40%

Less friction



75% less glycerine

Longer hose lifetime



Less maintenance

Pump up to 80% solids



Save water

Technical features

- Only the hose is in contact with the medium
- Positive displacement with no backflow
- Single roller design that enables minimized friction
- Low lubrication need, only 25% that of conventional peristaltic pumps
- No overheating at high continuous flow rate
- Dry run capability
- Selfpriming up to full vacuum






Flowrox pump technology

Flowrox pumps' rolling technology is capable of operating in continuous duty with its maximum pressure and maximum flow in the same point. This is where the conventional pump compromises either on pressure or flow.

Compared to Flowrox pumps, conventional hose pumps can only reach either half the flow or half the pressure in continuous duty.

What is more, Flowrox pumps can perform even with high temperature media up to 95 °C / 203 °F.

Flowrox hose pump technology vs. conventional technology



Patented adjustment mechanism senses hose wear when compression is readjusted. This helps to maximize hose lifetime and minimize the risk of over-compression. There is no need for shimming.

LPP-T pumps provide substantial savings through improved process performance and efficiency, long service intervals and low maintenance costs. They are manufactured using durable elastomers and advanced materials, making them perfect for pumping a wide range of media.

The LPP-T100 / LPP-T4" is one of the world's largest hose pumps, with a maximum continuous flow of 100m³/h / 440 gpm.

For transferring, dosing and metering

The innovative Flowrox peristaltic pumps set the industry standard for peristaltic pump technology. Designed for heavy industrial duties, Flowrox LPP-T and LPP-D pumps are ideal for pumping diverse slurries and dosing a wide range of

abrasive, corrosive, viscous or crystallizing media.

Progressive cavity pumps

Flowrox progressive cavity (PC) pumps are ideal for demanding industrial slurry and paste pumping applications, especially with highly viscous or shear sensitive liquids and sludges.

Advanced spiral technology

In PC pumps, the pumped medium continuously shifts spaces (progressing cavities) between the rotor and the stator, enabling nearly pulsation-free pumping. With Flowrox technology it is possible to deliver up to 10 bar / 150 psi of pressure per single stage. This is possible with our evenwall stator technology that forms the heart of the entire pump.

Customer benefits

- Over 30% higher pumping capacity compared to a conventional PC pump with same rpm
- Save energy up to 15% compared to a conventional model
- Minimized maintenance time enables the highest run time possible

Flowrox progressive cavity (PC) pumps from features to benefits

Advanced product structure



Longer maintenance interval

Evenwall® stator



Higher pressure with RPM

2/3 rotor geometry



30% higher flow with same speed

Technical features

- Combination of an elliptic rotor and a stator with even wall thickness
- More pressure with less strain
- Increased flow per revolution
- Long rotor/stator lifetime
- Less backflow



Through advanced technology and precise design, Flowrox PC Pumps offer you significant savings by reducing pumping costs.




Flowrox pump technology

Less RPM needed to achieve the same flowrate.

When the Flowrox PC pump performance is compared with conventional PC pumps, Flowrox 2/3 geometry pumping elements need less RPM than conventional 1/2 geometry pumping elements to achieve the same flow rate. Slower rotation speed guarantees less wear.

Flowrox pumps' spiral technology vs. conventional technology





Flowrox Expulse™ pulsation dampeners

We provide complementary equipment that is designed to support the optimal flow. Enhance your process with the Flowrox Expulse pulsation dampener.



Quiet and durable design

It is common for positive displacement pumps to produce pulsation. The Flowrox Expulse is a flexible inline pulsation dampener, which quiets noise

while settling pressure peaks and uneven flows. The design is based on a double hose structure with resilient inner hose, reinforced outer hose and compressed air between the hoses.

Flowrox Expulse

- Absorbs up to 90% of the pulsation
- Up to 10% energy savings
- Reduces hammering of the pipeline and makes pump bearings and gearboxes last longer
- All in one; flexible pipeline connection and dampener
- Can be installed on any pulsating pump from any brand
- There are no breaking diaphragms or bladders
- Flowrox Expulse is self-cleaning
- Does not collect sediment or particles

Flowrox Expulse from features to benefits

Reduces noise	→	Quiets the annoying noise of the pulsating pump in the pipelines
Saves energy	→	Absorbs up to 90% of pulsations and saves up to 10% of energy
Easy, independent and reliable	→	Easy to install for any pulsating pump
Protects pump bearings and gearbox	→	Reduces pipeline pulsations
Simple and flexible	→	Easy and fast to maintain

Technical features

- Absorbs up to 90% of pulsations
- Enables pump bearings and gearbox last longer
- Saves pumping energy up to 10%
- Easy to install on any pulsating pump type



Standard spare parts

With decades of experience in developing innovative flow control solutions and elastomer technology, we offer a wide selection of superior elastomers for diverse media and process conditions. The correct mechanical hose design and material selection are essential for optimizing hose lifetime.

Optimal pump hoses and tubes for each media


Our high-grade hose materials include chemical resistant ethylene propylene (EPDM), oil and fat resistant nitrile rubber (NBR), which is available also for food grade mediums (NBRF), and extremely abrasive natural rubber (NR), which is ideal for heavy wearing applications.

- To guarantee the best possible mechanical characteristics, the hose cover is always made of natural rubber.

LPP-T pump hose is preformed for easier installation



LPP-D pump hose construction



Auxiliaries

Revolution sensor & pressure transmitter


The revolution sensor calculates the cycles of the pump. Pressure transmitter can be used to detect overpressure of the pipeline.



The hose leak detector

The hose leak detector indicates hose leakage into pump housing. It automatically stops the rotation of the pump when connected to the control system.





Pump services

We offer prompt support, spare parts and services in order to maximize your pump performance.

We manufacture and supply rotors, stators, drive shafts, coupling rods, joint assemblies, bearings sets and sealings. Spare parts are manufactured according to highest quality and environment standards with over 20 years of experience.

A reliable partnership

Enjoy the benefits that come with selecting a partner that understands your process needs and unique challenges.

Our products provide industry-proven efficiency and reliability

based on well-thought-out designs and material selections paired with dedicated service expertise.

Full product assemblies with service coverage across their entire lifecycle, all from one responsible source, ensure optimized performance.

We offer:

- On-time trouble-free delivery of spares and services
- Cost savings through optimized service cycles and reduced downtime of equipment
- Longer life cycles for equipment



Customer benefits

- Maintenance for valves & pumps
- Specialised customer service
- Fast deliveries
- Wide selection of materials
- High-quality spare parts
- Service and warehousing agreements






Flowrox pump product portfolio




Pumps

Peristaltic pumps				
Product	Series	Design	Specifications	Application
Flowrox hose pumps, transfer pumps 	LPP-T-series	Advanced rolling design eliminates friction, maximizes hose life, lowers energy consumption	Size: DN32, 40, 50, 65, 80, 100 LPP-T1.25", 1.5", 2", 2.5", 3", 4" Volume: 0,5 – 100 m³/h / 2.2 - 440 gpm Pressure: 7,5 or 10 bar / 150 or 108 psi Solids: Up to 80 % Temperature: Up to 95 °C / 203 °F Particle size: 25 % from DN size Suction lift: 0 – 8 m / 0 – 26 ft capability	Toughest industrial applications such as thickener underflow, heavy duty slurry transfer, tailings transfer, sampling and dosing
Flowrox hose pumps, dosing pumps 	LPP-D-series		Size: DN15, 20, 25 LPP-D½", ¾", 1" Volume: 0,1 – 2 m³/h / 0 – 7.9 gpm Pressure: 7,5 or 16 bar / 108 or 232 psi Solids: Up to 80 % Temperature: Up to 95 °C / 203 °F Particle size: 25 % from DN size Suction lift: 0 – 8 m / 0 – 26 ft capability	

Pumps

Progressive cavity pumps				
Product	Series	Design	Specifications	Application
Flowrox progressive cavity pumps 	E-series	Advanced spiral technology, 2/3 rotor geometry, combination of an elliptic rotor and a stator with even wall thickness	Size: 2/10, 4/10, 10/10, 20/10, 35/10, 70/10, 150/10, 250/10 Volume: 0-170 m ³ /h / 0-747 gpm Pressure: Up to 10 bar / 150 psi 0 – 1000 gpm	Flooded suction duties e.g. paper coating and paste pumping
Flowrox progressive cavity pumps 	EL-series	Advanced spiral technology and 2/3 elliptic rotor geometry	Size: 50/6, 100/6, 200/6, 330/6 Volume: 0-268 m ³ /h / 0-1180 gpm Pressure: Up to 6 bar / 87 psi	Flooded suction duties e.g. municipal waste pumping
Flowrox progressive cavity pumps 	D-series	1/2 rotor geometry and compact size	Size: 004/12, 010/12, 025/12, 075/12 Volume: 0-1,5 m ³ /h / 0-66 gpm Pressure: Up to 12 bar / 175 psi	Flooded suction duties e.g. flocculant and chemical dosing

Auxiliaries

Complementary products			
Product	Design	Specifications	Application
<div>Flowrox Expulse pulsation dampener</div> <div></div>	All in one; flexible pipeline connection and dampener	<div>Size: DN32 – DN100 / 1.25" – 4"</div> <div>Hose: NR Standard</div> <div>Wetted parts: AISI316 & NR</div> <div>Pressure: 10 bar / 145 psi</div> <div>Temperature: +75 °C / +167 °F</div> <div>Filling media: Oil free compressed air</div> <div>Auxillaries: Flanges</div>	For hose pumps in applications where pulsation dampening is needed
<div>Revolution sensor & pressure transmitter</div> <div></div>		The revolution sensor calculates the cycles of the pump. Pressure transmitter can be used to detect overpressure of the pipeline.	For hose pumps
<div>Hose leak detector</div> <div></div>		The hose leak detector indicates hose leakage into pump housing. It automatically stops the rotation of the pump when connected to the control system.	For hose pumps

Standard spare parts

Standard spare parts		
Product	Specifications	Application
Hoses 	<ul style="list-style-type: none"> NR, EPDM, NBR, NBRF 	For transferring and dosing pumps
Spare parts and spare part kits 	<ul style="list-style-type: none"> Bearing sets Sealing sets 	For hose pumps
Rotors 	<ul style="list-style-type: none"> 1/2 and 2/3 geometry Black nitrated carbon steel Stainless steel Hard chrome plated Hardened Ceramic coated 	For PC pumps
Stators 	<ul style="list-style-type: none"> All materials e.g. NBR, EPDM, CSM, FPM 1/2 and 2/3 geometry 	For PC pumps
Shafts 	<ul style="list-style-type: none"> Drive shafts 	For centrifugal pumps
Bearing units 	<ul style="list-style-type: none"> Complete bearing assemblies 	For centrifugal pumps
Shaft seals 	<ul style="list-style-type: none"> Mechanical seals Sealing cords e.g. teflon and graphite 	For centrifugal pumps



Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Marssitie 1, 53600 Lappeenranta, Finland
+358 10 417 5000
www.valmet.com/flowcontrol

