



NOTE:

1) DIMENSIONS INCHES [mm]

- 2) UNIT HEIGHTS MAY VARY BY MODEL
 - UNIT HEIGHT; SHORT COVER W/O VISUAL INDICATOR = 3.26" [82.8 mm]
 - COVER REMOVAL CLEARANCE REQUIRED = 1.50" [38.1 mm]
 - UNIT HEIGHT; SHORT COVER W/ VISUAL INDICATOR = 3.96" [100.6 mm]
 - COVER REMOVAL CLEARANCE REQUIRED = 1.50" [38.1 mm]
 - UNIT HEIGHT; TALL COVER W/ VISUAL INDICATOR = 6.38" [162.1 mm]
 - COVER REMOVAL CLEARANCE REQUIRED = 3.32" [84.3 mm]

3) CONSULT FACTORY FOR COVER SIZE ON SPECIFIC MODELS.

4) CONSULT FACTORY FOR CONDUIT / CONNECTOR SIZE AND QUANTITY ON SPECIFIC MODELS.

5) CONSULT FACTORY FOR MOUNTING HOLE PATTERNS ON SPECIFIC MOUNTING SET APPLICATION. MOUNTING HARDWARE REQUIRED AND SOLD SEPERATELY.

REVISIONS	REVISION	ECO	DATE	BY	TITLE	DRAWING NO		REV	
	C	18887	10/5/22	RB	PUBLIC THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF AND IS SUBJECT TO CHANGE BY VALMET.	500134		C	
	B	16608	08/04/20	BK		500134		C	
	A	9837	06/24/14	JL		500134		C	
TOLERANCES* (UNLESS OTHERWISE SPECIFIED):					DR.	DIMENSIONAL DATA, PRISM, PI			
X.XXX ± .005 ANGLES ± 0° 30'					CHK.	SCALE	1:3	SHEET	1 OF 1
X.XX ± .010 FINISH f 125 RMS					APPD.	SIZE	A	DATE	6/24/2014
X/X ± .015 *DIMENSIONS: INCHES (UNLESS OTHERWISE SPECIFIED)									

CERTIFIED TO BE DIMENSIONALLY CORRECT.

Valmet

FERGUS FALLS, MN 56537 USA