

Power supplies

Model number
 PS459042A
 PS459046A (ETL)



8.0 amp 30 VDC power supply

This compact power supply is designed for use with dual channel AS-Interface gateways with single power supply feature. The 8.0 amp power supply provides power to both AS-Interface channels.

Features



- Current limited/short circuit protected
- Regulated to $\pm 1\%$
- ETL approved for Class I Division 2 (PS459046A)



Specifications	
Output voltage	30.05 VDC $\pm 1\%$
Output current	8.0 amps
Input voltage	120 / 240 VAC (47-63 Hz)
Displays	Power on, green LED
Current limits	12.0 amp (max)
Operating temperature	0° to +60°C (+32° to +140°F)
Storage temperature	-25° to +85°C (-13° to +185°F)
Housing	Al/Mg alloy, DIN rail mounting
Dimensions (L, W, H)	148mm, 70mm, 154mm
Ingress protection	IP20, field enclosure required
Weight	1200g (2.65 pounds)
Approvals (PS459046A)	ETL approved Class I, Division 2, groups A, B, C, D



Schematic drawing





Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Vanha Porvoontie 229
01380 Vantaa, Finland
flowcontrol@valmet.com
+358 10 417 5000
valmet.com/flowcontrol

**Valmet Flow Control Inc.
Stonel product center**

26271 US Hwy 59, Fergus Falls, MN 56537 USA.
Tel. +1 218 739 5774.
sales.stonel@valmet.com
valmet.com/flowcontrol

